



TECHNICAL SHEET


FA 40 500 15

Designation :

Restraint Kernmantle Rope Lanyard

- Made up of 12mm diam polyamide kernmantle rope.
- Abrasion resistant thimble to protect the loops from being damaged by metallic contact.
- Sewing protected with a strong transparent covering sleeve which protects the ends and also make stitches visible for easy inspection before the use.
- Breaking strength : 22 kN

Compliance : EN354 : 2002



Length :

Lg : 1,5 m

Material:

Lanyard: polyamide

Connector: steel

HS code

56075090

Carton Size/ Pieces

60x40x24 / 50

Unit Weight

0,20 kg

AET: N° 2577 Issue 2 Extension 2

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



Maj. : 07/13

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

